

## PERFORMANCE

### Panel

**Panel**

In-Plane Switching (IPS)

**Display Size**

21.5 inches (546.1mm)

**Max View Area**

WxH: 476.1 x 267.8 mm (18.74 x 10.54 inches)

**Native Resolution**

1920x1080

**Aspect Ratio**

16:9

**Pixel Pitch**

0.24795 x 0.24795 mm

**DPI**

102.4 dpi

**Brightness**

250 nits

**Contrast Ratio**

1000:1

**Pixel Response Time**

4 ms (extreme mode) / 6 ms (typical mode) / 14 ms (off mode)

**Color Gamut**

72% NTSC

**Viewing Angle**

Horizontal: +/- 89°, vertical: +/- 89°

**Anti-glare**

Anti-glare

### Multi-Media

**Camera**

720p, with dual microphone and LED indicator

**Microphone**

Dual array microphone

**Speakers**

Stereo speakers, 2W x2

### Power Supply

**Power Supply**

Power	Type	Efficiency	Key Features
90W	Adapter	88%	-

**Power Consumption**

19 watts typical, 32 watts max

## DESIGN

### Menu

**Presets and User Settings**

- Presets: 25

- User settings: 25

## On Screen Display

On screen display with digital user controls (8 languages)

## Display

### Touchscreen

(Optional)10-point multi-touch, supports Wake on Touch. ONLY for model 10R0PAT1 and 10R0PAR1.

## Mechanical

### Compatible Tiny

P330 / P320 / M920(x) / M720 / M910(x) / M710 / M900(x) / M700 / M630e / M625 / M600 / M75q / M715 / M93p / M83 / M73 / M53 / Chromebox Tiny

### Bezel Width

- Top / side: 2mm
- Bottom: 22.1mm

### Buttons

- Power button
- Exit button
- Menu button
- Mode-switching button
- Brightness button

### Cables

Undetachable 3-in-1 cable (power connector, USB [supports USB 3.1 Gen 1 / USB 2.0], DisplayPort™)

### Case Color

Black

### Dimensions (WxDxH)

Models	Dimensions
Models without stand	489 x 72.5 x 339 mm (19.26 x 2.85 x 13.35 inches)
Models with full function monitor stand	489.3 x 273.3 x 370.7 mm (19.26 x 10.76 x 14.59 inches)

### Weight

Models	Weight
Models without stand	3.19 kg (7.01 lbs)
Models with full function monitor stand	5.34 kg (11.77 lbs)

### Mounting

Supports VESA mount 100mm

### Stand

Full function monitor stand, supports -5° to +30° tilt, left & right 45° swivel, up to 150mm lift, -5° to +90° pivot

### In the Box

- TIO (monitor)
- Detachable stand
- Driver CD
- Power adapter
- Power cord
- Quick start and safety poster
- User's guide

## CONNECTIVITY

### Ports

#### Rear Ports

- 1x USB upstream port
- 1x DisplayPort
- 1x power connector

## Left Ports<sup>[1]</sup>

- 1x USB 3.1 Gen 1 (on TIO)
- Side ports offered by installed Tiny (on Tiny)

### Notes:

1. The availability and version depends on the Tiny installed or the PC connected via USB upstream port

## SERVICE

### Warranty

#### Base Warranty

3-year customer carry-in or mail-in via rapid replacement service

## CERTIFICATIONS

### Green Certifications

#### Green Certifications

- EPEAT™ Silver
- ENERGY STAR® 8.0
- TCO Certified 7.0
- TCO edge 2.0
- TÜV
- ULE Gold
- RoHS compliant
- VOC
- WEEE

### Other Certifications

#### Other Certifications

- FCC Class B
- ISO 9241-307
- TÜV Rheinland Eye Comfort Certification

